






# 4:3 FORMAT MONITOR SELECTION GUIDE

Product	Description / Model Number	Dimensions 19.0"xHxD	Avail. Color	Options
	<b>10.4" Display (5U) / RMM-101</b> 1024 x 768 max resolution, 16.2M colors. 500 cd/m <sup>2</sup> brightness, 1200:1 contrast. 176° Horizontal/Vertical viewing angles. Optional S-Video and composite video inputs. Supplied with Input cables and AC/DC adapter.	H=8.75" D=2.4"	Black	Lexan™(L) Video (V) Touchscreen (T)
	<b>10.4" Display (5U) / RMM-101S</b> 1024 x 768 max resolution, 16.2M colors. 500 cd/m <sup>2</sup> brightness, 1200:1 contrast. 176° Horizontal/Vertical viewing angles. Optional S-Video and composite video inputs. 24W integrated stereo speakers. Supplied with Input cables and AC/DC adapter.	H=8.75" D= 5.0"	Black	Lexan™(L) Video (V) Touchscreen (T)
	<b>DUAL 10.4" Display (5U) / RMM-102N</b> Specifications per screen: 1024 x 768 max resolution, 16.2M colors. 500 cd/m <sup>2</sup> brightness, 1200:1 contrast. 176° Horizontal/Vertical viewing angles. Optional S-Video and composite video inputs. Supplied with Input cables and AC/DC adapter.	H=8.75" D=2.35" (1.65" behind mounting rails).	Black	Lexan™(L) Video (V)
	<b>17" Display (1U) / RMM-607</b> 1280 x 1024 max resolution, 16.7M colors. 170° Horizontal / 160° Vertical viewing angles. 250 cd/m <sup>2</sup> brightness, 1000:1 contrast. Complete with lock-out ball bearing slides. Supplied with Input cables and AC/DC adapter. Optional S-Video and composite video inputs(V).	H=1.75" D=19.0"	Black	Lock (L) Retainer (R) Both( C) Video (V) Touchscreen (T)
	<b>17" Display (7U) / RMM-917</b> 1280 x 1024 max resolution, 16.7M colors. 170°/160° Horizontal/Vertical viewing angles. 250 cd/m <sup>2</sup> brightness, 1000:1 contrast. VGA and DVI-D inputs. Supplied with Input cable and AC/DC adapter. Optional S-Video and composite video inputs(V).	H=12.3" D=1.75"	Black	Lexan™(L) Video (V) Touchscreen (T)
	<b>19" Display (8U) / RMM-409N2</b> 1280 x 1024 max resolution, 16.7M colors. 170° Horizontal / 160° Vertical viewing angles. 250 cd/m <sup>2</sup> brightness, 5M:1 Dynamic contrast. VGA and DVI-D inputs. Supplied with VGA Input and power cables.	H=14.0" D=2.7"	Black	Lexan™(L)
	<b>19" Display (8U) / RMM-909</b> 1280 x 1024 max resolution, 16.7M colors. 178° Horizontal/Vertical viewing angles. 270 cd/m <sup>2</sup> brightness, 800:1 contrast. VGA and DVI-D inputs. Supplied with Input cable and AC/DC adapter. Optional S-Video and composite video inputs(V).	H=14.0" D=1.7"	Black	Lexan™(L) Video (V) Touchscreen (T)
	<b>20.1" Display (8U) / RMM-420</b> 1600 x 1200 max resolution, 16.7M colors. 178° Horizontal/Vertical viewing angle. 300 cd/m <sup>2</sup> brightness, 800:1 contrast. 8ms GTG Response time. VGA and DVI-D inputs, internal power supply. Supplied with Input and power cables.	H=14.0" D=3.3"	Black	Lexan™(L)

Features and specifications subject to change without notice.

**RECORTEC, INC.**

www.recortec.com  
sales@recortec.com

**1-800-729-7654**

3329 Kifer Road Santa Clara, CA 95051  
Tel: 408-928-1480 Fax: 408-928-1489