

19" RACK MOUNT LCD MONITOR



- Mounts in 8U (14.0") of vertical 19" rack space.
- 19" TFT LCD display with 1280 x 1024 resolution.
- Steel front panel construction with a durable powder coat finish.
- LED Backlight provides high contrast ratios and energy savings.
- Analog and Digital inputs.

GENERAL SPECIFICATIONS

Dimensions:

19.0" (W) x 14.0" (H) x 2.7" (D)

Weight:

10.5 lbs.

Power:

100 - 240 VAC, 50/60 Hz.
25 Watts typ.

On-Screen Controls:

Brightness, Contrast, Horizontal & Vertical
Position, Auto Adjust, OSD H & V Position, Input Select
Color Temp., Reset.

Plug & Play:

DDC/C1 and DDC2B

Temperature:

Operating: 10°C to 40°C
Storage: -20°C to 45°C

Humidity:

Operating: 10 to 80% RH (max)

Input Signal (VGA):

R.G.B. analog video, TTL H & V sync.

Input Signal (Digital):

DVI-D (HDCP).

Input Connectors:

Analog: 15-pin mini D-Sub.
Digital: 24 pin DVI-D.

Colors Available:

Black.

DISPLAY SPECIFICATIONS

Display Type:

Active matrix TFT LCD

Display area:

18.5" Diagonal.

Colors Displayed:

16.7 million colors.

Contrast Ratio:

1000:1 / 5M:1 DFC

Brightness:

250 cd/m² typ.

Backlight:

LED 4 Channel

Viewing Angle (CR>10):

Horizontal: 170°
Vertical: 160°

Response Time:

5ms

Resolution:

VGA up to 1280 x 1024.

Horizontal Frequency:

30 to 83 KHz.

Vertical Frequency:

56 to 75 Hz.

Specifications subject to change without notice.

MODEL NUMBER

RMM-409N2

RMM-409N2/L (with Lexan™ screen protection)

Offering OEM and custom solutions.
Contact us for additional information.



RECORTEC, INC.

www.recortec.com

sales@recortec.com

1-800-729-7654

3329 Kifer Road
Santa Clara, CA 95051

Tel: 408-928-1480
Fax: 408-928-1489