

# 20.1" RACK MOUNT LCD MONITOR



- 20.1" TFT LCD display with 1600 x 1200 resolution.
- Steel construction with a durable powder coat finish.
- Wide viewing angle offers mounting flexibility.
- Optional Lexan™ screen protection.
- Mounts in 8U of 19" rack space.
- Analog and Digital inputs.

## GENERAL SPECIFICATIONS

### Dimensions:

19.0" (W) x 14.0" (H) x 3.3" (D)

### Weight:

18.0 lbs.

### Power:

100 - 240 VAC, 50/60 Hz.

58 Watts typ.

### On-Screen Controls:

Brightness, Contrast, Horizontal & Vertical Position, Auto Adjust, OSD H & V Position, Input Select, Color Temp., Reset.

### Plug & Play:

DDC1 and DDC2B

### Temperature:

Operating: 10°C to 40°C

Storage: -20°C to 45°C

### Humidity:

Operating: 10 to 80% RH (max)

### Input Signal (VGA):

R.G.B. analog video, TTL H & V sync.

### Input Signal (Digital):

DVI-D (TDMS).

### Input Connectors:

Analog: 15-pin mini D-Sub.

Digital: 24 pin DVI-D.

### Colors Available:

Black.

## DISPLAY SPECIFICATIONS

### Display Type:

Active matrix TFT LCD

### Display area:

20.1" Diagonal.

### Colors Displayed:

16.7 million colors.

### Contrast Ratio:

800:1

### Brightness:

300 cd/m<sup>2</sup> typ.

### Viewing Angle (CR>5):

Horizontal: 178°

Vertical: 178°

### Response Time:

8 ms GTG.

### Resolution:

VGA up to 1600 x 1200.

Specifications subject to change without notice.

## MODEL NUMBER

**RMM-420**

**RMM-420L** with Lexan™ screen protection.



Offering OEM and custom solutions.  
Contact us for additional information.

**RECORTEC, INC.**

[www.recortec.com](http://www.recortec.com)

[sales@recortec.com](mailto:sales@recortec.com)

**1-800-729-7654**

3329 Kifer Road  
Santa Clara, CA 95051

Tel: 408-928-1480  
Fax: 408-928-1489