

23" 16:9 FULL HD MONITOR



- Mounts in 8U of rack space with mounting brackets to fit 19" rack width.
- 23" Wide format TFT LCD display with full HD 1920 x 1080 resolution.
- LED backlight and super wide 178/178 degree viewing angles.
- 1080p 16:9 aspect ratio provides a widescreen viewing area.
- 20,000,000:1 Dynamic contrast ratio for superior detail.

GENERAL SPECIFICATIONS

Dimensions:

22.75" (W) x 14.0" (H) x 3.0" (D)

Weight:

17.0 lbs.

Power:

100 - 240 VAC, 50/60 Hz.

45 Watts typ.

Plug & Play:

DDC2B

Temperature:

Operating: 0°C to 40°C

Storage: -20°C to 45°C

Humidity:

Operating: 20 to 90% RH (non-condensing)

Input Video Signals:

R.G.B. analog, DVI (with HDCP)

Input Frequency:

Fh: 22-82 KHz, Fv: 50-75 Hz.

Sync Type:

Separate H/V, Composite H/V, SOG.

Input Connectors:

15 pin D-sub, DVI-D.

Compatibility:

PC/Windows, Macintosh.

Colors Available:

Black.

DISPLAY SPECIFICATIONS

Display Type:

TFT active matrix with IPS LCD.

Viewable Size:

23.0" diagonal.

Colors Displayed:

16.7 million colors.

Contrast Ratio (Typ/Dyn):

1000:1 / 20,000,000:1

Brightness:

250 cd/m² typ.

Viewing Angles:

178°/178° H/V.

Response Time:

6 ms Typ.

Optimum Resolution

1920 x 1080 non-interlaced.

Light Source:

LED

Long Life (30,000 hrs typ).

Panel Surface:

Anti-glare.

Specifications subject to change without notice.

MODEL NUMBER

RMM-423HD



RMM-423HD shown mounted in a standard 19" equipment rack.

RECORTEC, INC.

www.recortec.com

sales@recortec.com

1-800-729-7654

3329 Kifer Road
Santa Clara, CA 95051

Tel: 408-928-1480
Fax: 408-928-1489