

23" 16:9 FULL HD MONITOR



- Mounts in 8U of rack space with mounting brackets to fit 19" rack width.
- 23.0" 16:9 format TFT LCD display with full HD 1920 x 1080 resolution.
- Fast video response time provides sharp text and crisp motion.
- IPS LCD panel provides wide viewing angles (U/D, L/R).
- 1000:1 Static contrast ratio for superior detail.

GENERAL SPECIFICATIONS

- Dimensions:**
22.75" (W) x 14.0" (H) x 3.0" (D)
- Weight:**
17.0 lbs.
- Power:**
100 - 240 VAC, 50/60 Hz.
45 Watts typ.
- Plug & Play:**
DDC2B
- Temperature:**
Operating: 0°C to 40°C
- Humidity:**
Operating: 20 to 90% RH (max)
- Input Video Signals:**
R.G.B. analog, DVI (with HDCP)
- Input Frequency:**
Fh: 22-82 KHz, Fv: 50-75 Hz.
- Sync Type:**
Separate H/V, Composite H/V, SOG.
- Input Connectors:**
15 pin D-sub, DVI-D.
- Compatibility:**
PC/Windows, Macintosh.
- Colors Available:**
Black.

Offering OEM and custom solutions.
Contact us for additional information.

DISPLAY SPECIFICATIONS

- Display Type:**
TFT active matrix with IPS LCD.
- Viewable Size:**
23.0" diagonal.
- Colors Displayed:**
16.7 million colors.
- Contrast Ratio :**
1000:1.
- Brightness:**
300 cd/m² typ.
- Viewing Angles:**
178°/178° H/V.
- Response Time:**
14 ms Typ.
- Optimum Resolution**
1920 x 1080.
- Light Source:**
Long Life (50,000 hrs typ).
- Panel Surface:**
Anti-glare.
- Specifications subject to change without notice.

MODEL NUMBER

RMM-423HD



RMM-423HD shown mounted in a standard 19" equipment rack.

RECORTEC, INC.

www.recortec.com
sales@recortec.com

1-800-729-7654

1650-A Berryessa Rd Tel: 408-928-1480
San Jose, CA 95133 Fax: 408-928-1489