

1U 17" LCD MONITOR WITH CHERRY™ KEYBOARD AND TOUCHPAD



- Monitor and Cherry™ keyboard with two button touchpad in 1U of rack space for 19" racks.
- Mounted with included smooth action ball bearing slides which lock in the extended position.
- Monitor powers off preserving back light life when tilted down for sliding into the rack.
- Retainer and lock options to keep unit contained in the rack when not in use.
- Housed in rugged steel construction with a durable powder coat finish.
- Monitor surface protected by a clear unbreakable Lexan™ covering.

DISPLAY SPECIFICATIONS

Display Type:	Active matrix TFT LCD	Resolution:	640 x 350
Colors:	16.7 million colors		640 x 480
Contrast Ratio:	1000:1 typ.		800 x 600
Brightness:	280 cd/m ² typ.		1024 x 768
Viewing Angle:	Horizontal: 178° Vertical: 178°	Display Area:	1280 x 1024 (17")
Response Time:	25ms.	Horizontal Frequency:	31.5 to 80 KHz
		Vertical Frequency:	56 to 75 Hz.

GENERAL SPECIFICATIONS

Dimensions:	19.0" (W) x 1.75" (H) x 25.75" (D)
Weight:	27 lbs
Power (TFT Display):	90 - 260 VAC, 50/60 Hz. 60 Watts maximum
On-Screen Controls:	Brightness, Contrast, Horizontal & Vertical Position, Auto Adjust, OSD H & V Position, Load and Save Values
Plug & Play:	DDC1 and DDC2B
Temperature:	Operating: 0°C to 50°C Storage: -20°C to 60°C
Humidity:	Operating: 10 to 85% RH (max)
Input Signal (VGA):	R.G.B. analog video, TTL H & V sync.
Input Connector:	Display: 15-pin mini D-Shell
Colors Available:	Choice of Black (B) or Light Gray.

KEYBOARD AND TOUCHPAD SPECIFICATIONS

Rollover:	Alpha N-key rollover.
Auto repeat:	Yes.
Self Diagnostics:	At power on and system reset.
Data Buffer:	All codes buffered before sending.
Operating voltage:	+5 VDC +/- 5%.
Operating current:	200 mA.
Touchpad Size:	2.2" X 1.6"
Buttons:	Left and Right.
Interface:	Keyboard: PS/2. Touchpad: PS/2.
Compatibility:	DOS, Windows 3.X, Windows 95/98, Windows NT, Windows 2000,XP.

Specifications subject to change without notice.

This unit is recommended for use with KVM switches.

Contact us about other options and additional rack mount products.



MODEL NUMBER

RMM-627(X)

_____	Blank = Standard Front Panel
_____	R = Front Panel + Retainer Screws
_____	L = Front Panel + Lock
_____	C = Front panel + Lock + Retainer Screw

Tel: 408-928-1480
web:www.recortec.com
1650 Berryessa Road

RECORTEC, INC.
1-800-729-7654

Fax: 408-928-1489
email:sales@recortec.com
San Jose, CA 95133